










# PRODUCT OVERVIEW

## WELDING GAUGES

Image	Item no.	Model	Angle of preparation	Measurement range	Reading	Weight
	35163270	<b>A</b>	-	Welding seam height 4 - 12 mm 90° angles		80 g
	35160125	<b>B</b>	-	0 - 20,0 mm	0 - 25,0 mm	80 g
	35161250	<b>C</b>	-	0 - 25,0 mm	0,01 mm	140 g
	35162265 35162280	<b>D</b> D certificate incl.	0 - 60°	Welding seam: 0 - 20 mm	Welding arm height: 0 - 40 mm	106 g
	35162320	<b>E</b>	0 - 60°	A-seam: 0 - 15 mm	1 mm	135 g
	35162335	<b>E2</b>	0 - 60°	A-seam: 0 - 25 mm	Accuracy: ± -0,50 mm	140 g
	35162338	<b>F</b>	-	30 - 150°	Protractor 30-90°	140 g
	35162340	<b>G</b>	-	Accuracy: ± -0,10 mm	0,2 mm	140 g
	35162345	<b>H</b>	-	Butt weld measurement: 0 - 3 mm	-	75 g
	35162350	<b>I</b>	-	Seam control: Internal 0 - 30 mm	-	58 g
	35162353	<b>I2</b>	-	Seam control: 0 - 35 mm	Edge displacement, mm and inch-scale	160 g
	35162355	<b>J</b>	-	Range: ± 0,6 mm. 25 mm ruler, 1,5 og 3,0 holes	-	45 g
	35162360	<b>K</b>	-	28 sizes	-	150 g
	35162363	<b>K2</b>	-	A-seam: 0-1" Welding leg length: 1/8 - 1"	Inch-scale	150 g
	35163270	<b>L</b>	-	Control of undercuts 0 - 2 mm		30 g